

# FORMAX<sup>®</sup>

Div. of BESCORP, Inc.

## AutoSeal<sup>®</sup> FD 1500

PRESSURE SEALER

### Standard Features

- **Drop-In Feed System:** A drop-in three roller feed system produces dependable feeding of forms with no paper fanning required
- **14" Form Length Capability:** Flexibility to process even and uneven panel forms up to 14" in length
- **Desktop Design:** A sleek desktop design made with office usage in mind
- **L.E.D. Indicators:** Notifies an operator when the power is on, a cover is open, the paper runs out and if a fault occurs
- **Fold Types:** Folds "Z", uneven "Z", "C", half folds and custom forms

### Options:

- **Six-Digit Resettable Counter:** For maximum audit control
- **Extended Fold Plate:** For processing 14" uneven "C" paneled forms.\*
- **18" Conveyor w/ Photo Eye:** Allows for neat and sequential stacking
- **Locking Cabinet:** Fully enclosed for storage
- **400 Series Jogger:** Reduces static electricity and aligns forms for proper feeding
- **FD 1500-35 Reverse Stacking Conveyor:** Allows for A-to-Z input and A-to-Z output.

\* See Reverse



Shown with optional cabinet

The FD 1500 AutoSeal is *The* low volume folder/sealer solution for processing one-piece pressure sensitive mailers. Built with proven Formax technology, the FD 1500 provides an economical solution with the quality and reliability you have come to expect from Formax. The sleek office design and ease of operation makes this unit ideal for processing documents in an office environment with low volume applications. A processing speed of up to 85 forms per minute enables operators to complete daily processing jobs with ease. The added capability of processing 14" forms gives the FD 1500 the versatility needed to fold and seal virtually any low volume application to meet your needs.

**Formax a Division of Bescorp, Inc.**

New Hampshire, USA

Web Site: [www.formax.com](http://www.formax.com)

**LOCAL DEALER:**

## Flexible

The FD 1500 handles a variety of even panel forms up to 8 1/2" x 14" including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form. An optional extended fold plate is available for processing uneven panel forms up to 8 1/2" x 14".

## Dependable & Powerful


The FD 1500 is built with proven Formax technology. Heavy-duty steel construction offers the dependability and power expected of a larger unit in a smaller package. A processing speed of up to 85 forms per minute enables an operator to complete daily jobs in no time.



User Friendly Control Panel

## Pressure Seal Solution

The AutoSeal® FD 1500, combined with a laser printer and pressure seal forms, creates a secure, time saving and efficient solution for paper processing.



Standard "Z" Fold Process

## Ease of Operation

The FD 1500 is designed for user friendly operation. Simply set your folds according to the clearly marked settings on the fold plates, load your forms using the drop-in feed system, press start and you're on your way. A conveniently located LED indicator lights up notifying the operator when a cover is open, the paper is out, or a fault occurs.

## Specifications:

|                    |  |
|--------------------|--|
| Hopper Capacity:   | Up to 100 Sheets 24# (90gsm)   |
| Fixed Speed:       | Up to 85 sheets per minute - based on 11"(279mm) "Z" fold  |
| Paper Size:        | Up to 8.5" W x 14" L (216 W x 356 L mm)  |
| Power:             | FD Model: 120 Volts AC 50/60Hz<br>FE Model: 220 Volts AC 50/60Hz   |
| Duty Cycle:        | Up to 4,000 per week   |
| Dimensions:        | 24" L x 17" W x 13" H (61 L x 43 W x 33 H cm)  |
| Weight:            | 82 lbs (37 kg)   |
| Document Sequence: | Standard sequence is A-to-Z input, Z-to-A output.<br>Optional FD 1500-35 reverse conveyor available for A-to-Z output. |
| Certifications:    | UL and CUL approved CE applied for   |

\* Extended fold plate is needed to process uneven "C" forms. Uneven "Z" forms with a minimum address panel of 3" can be processed without fold plate upgrade.



**A 400 Series Jogger** is a recommended option that reduces static electricity from forms and aligns them for proper feeding

# FORMAX<sup>®</sup>

Div. of BESCORP, Inc.

## AutoSeal<sup>®</sup> FD 2000

PRESSURE SEALER

### Standard Features

- **Drop-In Feed System:** A drop-in three roller feed system produces dependable feeding of forms with no paper fanning required.
- **Six-Digit Resettable Counter:** Provides maximum audit control.
- **Paper Jog Control:** Allows operators to jog forms through before operation.
- **14" Form Length Capability:** Flexibility to process even and uneven panel forms up to 14" in length.
- **Desktop Design:** A sleek desktop design made with office usage in mind.
- **L.E.D. Indicators:** Notifies the operator when the power is on, a cover is open, the paper runs out and if a fault occurs.
- **Noise Reduction:** Top and side covers are insulated to reduce operating noise.
- **Fold Types:** "Z", uneven "Z", "C", half folds and custom forms.

### Options:

- **P2000:** Cost saving package that includes the FD 2000, 18" conveyor and cabinet.
- **4' High Capacity Conveyor w/ Photo Eye:** Allows for neat and sequential stacking of up to 1,500 processed forms.
- **18" Conveyor w/ Photo Eye:** Allows for neat and sequential stacking.
- **Locking Cabinet:** Fully enclosed for storage
- **400 Series Jogger:** Reduces static electricity and aligns forms for proper feeding
- **FD 2000-35 Reverse Stacking Conveyor:** Allows for A-to-Z input and A-to-Z output.

**Formax a Division of Bescorp, Inc.**

New Hampshire, USA

Web Site: [www.formax.com](http://www.formax.com)

**LOCAL DEALER:**



*Shown with optional cabinet and 18" conveyor*

The AutoSeal<sup>®</sup> FD 2000 folder/sealer is a powerful desktop model designed to process your pressure sensitive self-mailers. An easy to use touch-pad control panel and three roller feed system makes this product both practical and dependable. Up to 150 forms can be loaded in the hopper and processed at speeds up to 7,000 per hour. The FD 2000 also comes with an optional fully enclosed cabinet for storage and a conveyor with photo-eye for neat and sequential stacking of processed forms.

## Flexible

The FD 2000 handles a variety of documents up to 8 1/2" x 14" including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form.

## Powerful


The FD 2000 processes forms at a rate of up to 7,000 sheets per hour and can hold up to 150 - 24# forms in the feed hopper. Combined with a duty cycle of up to 25,000 forms per month, the FD 2000 offers an economical and reliable solution for departmental post processing.



User friendly control panel

## Pressure Seal Solution

The AutoSeal® FD 2000 combined with a laser printer and pressure seal forms create a secure, time saving and efficient solution for paper processing.



Standard "Z" Fold Process

## Ease of Operation

The FD 2000 is set up for user friendly operation. Simply set your folds according to the clearly marked settings on the fold plates, load your forms, press start and you're on your way. The FD 2000 has indicators for power on, fault detection, paper out and cover open for operator convenience. It also includes a six-digit counter for audit control.



Standard Catch Tray

## Specifications:

|                            |  |
|----------------------------|--|
| Hopper Capacity:           | Up to 150 Sheets 24# (90gsm)   |
| Fixed Speed:               | Up to 7,000 sheets per hour - based on 11"(279mm) "Z" fold   |
| Paper Size:                | Up to 8.5" W x 14" L (216 W x 356 L mm)  |
| Power:                     | FD Model: 120 Volts AC 50/60Hz<br>FE Model: 220 Volts AC 50/60Hz   |
| Duty Cycle:                | Up to 25,000 per month   |
| Dimensions:                | 25.75" L x 16.5" W x 14.25" H (65 L x 42 W x 36 H cm)  |
| W/ 18" Conveyor & Cabinet: | 46" L x 22" W x 44" H (117 L x 56 W x 112 H cm)  |
| Weight:                    | 88.5 lbs (40 kg)   |
| Document Sequence:         | Standard sequence is A-to-Z input, Z-to-A output.<br>Optional FD 2000-35 reverse conveyor available for A-to-Z output. |
| Certifications:            | UL and CUL approved CE applied for   |



**A 400 Series Jogger** is a recommended option that reduces static electricity from forms and aligns them for proper feeding

# FORMAX<sup>®</sup>

Div. of BESCORP, Inc.

## AutoSeal<sup>®</sup> FD 2030

PRESSURE SEALER

### Standard Features

- **Drop-In Feed System:** A drop-in three roller feed system produces dependable feeding of forms with no paper fanning required
- **Six-Digit Resettable Counter:** Provides maximum audit control
- **Paper Jog Control:** Allows operators to jog forms through before operation
- **14" Form Length Capability:** Flexibility to process even and uneven panel forms up to 14" in length
- **Desktop Design:** A sleek desktop design made with office usage in mind
- **L.E.D. Indicators:** Notifies an operator when the power is on, a cover is open, the paper runs out and if a fault occurs
- **Noise Reduction:** Top and side covers are insulated to reduce operating noise
- **Fold Types:** Folds "Z", uneven "Z", "C", half folds and custom forms

### Options:

- **P2030:** Cost saving package that includes the FD 2030, 18" conveyor and cabinet
- **4' High-Capacity Conveyor w/ Photo Eye:** Allows for neat and sequential stacking of up to 1,500 processed forms
- **18" Conveyor w/ Photo Eye:** Allows for neat and sequential stacking
- **Locking Cabinet:** Fully enclosed for storage
- **400 Series Jogger:** Reduces static electricity and aligns forms for proper feeding
- **FD 2000-35 Reverse Stacking Conveyor:** Allows for A-to-Z input and A-to-Z output.



*Shown with optional cabinet and 18" conveyor*

The FD 2030 AutoSeal<sup>®</sup> desktop pressure sealer provides a reliable and compact solution for processing pressure sensitive self-mailers. Standard features include a six-digit counter, jog control, fault detection, L.E.D. indicators and an operator friendly touch-pad control panel. Up to 225 forms can be loaded in the feeder and processed at speeds up to 9,000 per hour. All of these features make the FD 2030 the perfect solution for streamlining your post processing. The FD 2030 is also available with an optional fully enclosed cabinet for storage, and a choice of two conveyors with photo-eye for neat and sequential stacking of processed forms.

**modular**  
MAILING SYSTEMS

Serving Tampa, Ft. Myers, Orlando,  
Jacksonville, Tallahassee & Southern GA  
(800) 881-MAIL • [www.modularmailing.com](http://www.modularmailing.com)

## Flexible

The FD 2030 handles a variety of documents up to 8 1/2" x 14" including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form.

## Powerful


The FD 2030 processes forms at a rate of up to 9,000 sheets per hour and can hold up to 225 - 24# forms in the feed hopper. Combined with a duty cycle of up to 75,000 forms per month the FD 2030 offers the ultimate solution for streamlining your in-office paper processing.



User Friendly Control Panel

## Pressure Seal Solution

The AutoSeal® FD 2030, combined with a laser printer and pressure seal forms, creates a secure, time saving and efficient solution for paper processing.



Standard "Z" Fold Process

## Easy to Operate

The FD 2030 is designed for user friendly operation. Simply set your folds according to the clearly marked settings on the fold plates, load your forms, press start and you're on your way. The FD 2030 has indicators for power on, fault detection, paper out and cover open for operator convenience. It also includes a six-digit counter for audit control.



Standard Catch Tray

## Specifications:

|                            |  |
|----------------------------|--|
| Hopper Capacity:           | Up to 225 Sheets 24# (90gsm)   |
| Fixed Speed:               | Up to 9,000 sheets per hour - based on 11"(279mm) "Z" fold   |
| Paper Size:                | Up to 8.5" W x 14" L (216 W x 356 L mm)  |
| Power:                     | FD Model: 120 Volts AC 50/60Hz<br>FE Model: 220 Volts AC 50/60Hz   |
| Duty Cycle:                | Up to 75,000 per month   |
| Dimensions:                | 25.75" L x 16.5" W x 14.25" H (65 L x 42 W x 36 H cm)  |
| W/ 18" Conveyor & Cabinet: | 46" L x 22" W x 44" H (117 L x 56 W x 112 H cm)  |
| Weight:                    | 88.5 lbs (40 kg)   |
| Document Sequence:         | Standard sequence is A-to-Z input, Z-to-A output.<br>Optional FD 2000-35 reverse conveyor available for A-to-Z output. |
| Certifications:            | UL and CUL approved CE applied for   |

U.S. Patents 5,772,841 , 5,865,925 , 5,968,308 & 6,264,592 Other Patents Pending

9/2005



A **400 Series Jogger** is a recommended option that reduces static electricity from forms and aligns them for proper feeding

# FORMAX<sup>®</sup>

Div. of BESCORP, Inc.

## AutoSeal<sup>®</sup> FD 2052

PRESSURE SEALER

### Standard Features

- **Drop-In Feed System:** A drop-in three roller feed system produces dependable feeding of forms with no paper fanning required
- **Variable Speed Control:** Up to 11,000 pieces per hour
- **Pre-programmed for 3 popular folds:** Accordion "Z" fold, letter "C" fold and single half fold in 11" & 14" (Int'l Size A4)
- **17" Form Capability:** Flexibility to process forms up to 17" (432mm) in length
- **Programmable Job Settings:** Set and store up to nine custom jobs
- **Fault Detector:** Detects double feeding and any faults
- **6-Digit Resettable Counter:** Provides maximum audit control
- **Batch Counting:** Allows for preset counts of documents to be processed
- **Noise Reduction:** Top and side covers are insulated to reduce operating noise
- **Fold Types:** "Z", uneven "Z", "C", Half and custom folds

### Options:

- **P2052:** Cost saving package that includes the FD 2052, 18" conveyor and cabinet
- **4' High-Capacity Conveyor w/Photo Eye:** Allows for neat and sequential stacking of up to 1,500 processed forms
- **18" Conveyor w/Photo Eye:** Allows for neat and sequential stacking
- **Locking Cabinet:** Fully enclosed for storage
- **Big Bin Paper Stacking Cart:** Safely and securely transports documents
- **400 Series Jogger:** Reduces static electricity and aligns forms for proper feeding
- **FD 2000-35 Reverse Stacking Conveyor:** Allows for A-to-Z input and A-to-Z output.



Shown with optional cabinet and 18" conveyor

The AutoSeal<sup>®</sup> FD 2052 is a fully automatic pressure sealer which provides the ultimate solution for processing pressure sensitive self-mailers. Designed with ease of operation and efficiency in mind, the FD 2052 automatically detects and adjusts for 11" and 14" (Int'l Size A4) paper sizes and is pre-programmed for three popular folds: "Z", "C" and Half. The FD 2052 also has the ability to store up to nine custom fold settings with the simple touch of a button.

The feed hopper can hold up to 350 forms which are processed at speeds up to 11,000 per hour. These features combine to make the FD 2052 an ideal solution for streamlining your post processing. Options include a fully enclosed cabinet for storage, an 18" (46cm) or 4' (122cm) high-capacity conveyor with photo eye for sequential stacking of processed forms, and a 400 Series Jogger to align forms for proper feeding.

**modular**  
MAILING SYSTEMS

Serving Tampa, Ft. Myers, Orlando,  
Jacksonville, Tallahassee & Southern GA  
(800) 881-MAIL • www.modularmailing.com

## Flexible

The FD 2052 handles a variety of documents up to 8.5”(216mm) x 17” (432mm) including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form.

## Powerful


The FD 2052 processes forms at a rate of up to 11,000 sheets per hour and can hold up to 350 - 24#(90 gsm) forms in the feed hopper. Combined with a duty cycle of up to 125,000 forms per month, the FD 2052 offers the ultimate solution for streamlining your paper processing.



User Friendly Control Panel

## Pressure Seal Solution

The AutoSeal® FD 2052, combined with a laser printer and pressure seal forms, creates a secure, time saving and efficient solution for paper processing.



Standard "Z" Fold Process

## Easy to Operate

The FD 2052 sets a new standard in pressure seal ease-of-use. “Z”, “C” and half folds for 11” and 14” (A4) forms are automatically set with the touch of a button. Up to nine custom folds can be stored into memory eliminating the need for manual setup of non-traditional pressure seal forms. The user-friendly control panel features LED indicators and a six-digit resettable counter.

## Specifications:

|                            |  |
|----------------------------|--|
| Hopper Capacity:           | Up to 350 Sheets 24# (90gsm)   |
| Fixed Speed:               | Up to 11,000 sheets per hour - based on 11”(279mm) “Z” fold  |
| Paper Size:                | Up to 8.5” W x 17” L (216 W x 432 L mm)  |
| Power:                     | FD Model: 120 Volts AC 50/60Hz<br>FE Model: 220 Volts AC 50/60Hz   |
| Duty Cycle:                | Up to 125,000 per month  |
| Dimensions:                | 29.5” L x 16.75” W x 14” H (75 L x 43 W x 36 H cm)   |
| W/ 18” Conveyor & Cabinet: | 46” L x 20” W x 44” H (117 L x 51 W x 112 H cm)  |
| Weight:                    | 99.5 lbs (45 kg)   |
| Document Sequence:         | Standard sequence is A-to-Z input, Z-to-A output.<br>Optional FD 2000-35 reverse conveyor available for A-to-Z output. |
| Certifications:            | UL and CUL approved CE applied for   |



Standard Catch Tray



A **400 Series Jogger** is a recommended option that reduces static electricity from forms and aligns them for proper feeding

# FORMAX<sup>®</sup>

Div. of BESCORP, Inc.

## FD 2052IL System

PRINT, FOLD & SEAL IN-LINE

### Standard Features

- **Print, Fold and Seal:** One-step process eliminates excess document handling
- **Document Security:** Enclosed paper path from the printer to pressure sealer ensures security. Ideal for PIN notices or other confidential applications
- **Form Capabilities:** Processes forms up to 14" in length
- **Printer Compatibility:** Designed to work with HP/Troy 4200, 4250, and 4350 laser printers with two 500-sheet paper trays. A list of other compatible models is available.
- **Installation:** Easy to install, no software required
- **Alignment Base:** Special alignment base holds the printer and pressure sealer securely and slides apart for easy access to the paper path and fold plates
- **Pre-Programmed for 3 Popular Folds:** Automatic fold plate setup for Z, C \*, Half and custom folds
- **Custom Folds:** Stores up to 9 different custom folds into memory
- **Fault Detector:** Detects double feeding and any faults
- **Dedicated Use:** Designed for in-line use only

### Options:

- **P2052IL:** Cost-saving package that includes FD 2052IL System, 18" conveyor and 2 cabinets
- **4' High-Capacity Conveyor w/Photo Eye:** Allows for neat and sequential stacking of up to 1,500 processed forms
- **18" Conveyor w/Photo Eye:** Allows for neat and sequential stacking
- **Locking Cabinets:** Fully enclosed for storage (2 cabinets required)

\* C-Fold bottom check position only

**Formax a Division of Bescorp, Inc.**

New Hampshire, USA

Web Site: [www.formax.com](http://www.formax.com)

**LOCAL DEALER:**



*FD 2052IL System shown with IL Pressure Sealer and IL Alignment Base, laser printer (not included), optional conveyor and optional locking cabinets*

### Secure Processing of One-Piece Mailers

The FD 2052IL System allows operators to print, fold and seal pressure-sensitive one-piece mailers in one step, reducing processing time while increasing document security and confidentiality. The IL System works in-line with model-specific MICR and Non-MICR desktop laser printers.

The IL System incorporates the industry-leading fully-automatic FD 2052 AutoSeal™ which features six automatic fold settings, a user-friendly LED control panel and the ability to store up to 9 custom folds into memory. The FD 2052IL is ideal for companies processing multiple fold types or for those who need a robust, desktop solution for larger mailings.

## Flexible

The FD 2052IL System handles a variety of documents up to 8.5" x 14" including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form.

## Easy to Operate


The AutoSeal IL System is easily installed. An IL-compatible desktop laser printer (see Specifications, below) is placed on the IL-Alignment Base with the FD 2052IL pressure sealer using placement guides to ensure proper alignment. The IL Alignment Base incorporates an easy-pull system which allows the printer to be pulled away from the FD 2052IL to provide convenient access to the paper path and fold plates.



User Friendly Control Panel

## Pressure Seal Solution

The AutoSeal® FD 2052IL System, combined with a laser printer and pressure seal forms, creates a secure, time-saving and efficient solution for paper processing.



Standard "Z" Fold Process

## Powerful

The FD 2052IL sets a new standard as the first heavy-duty tabletop pressure sealer capable of running in-line with laser printers. The FD 2052IL processes up to 175,000 forms per month in a compact and powerful design. The user-friendly control panel features LED indicators and a six-digit resettable counter.

## Specifications:

|   |  |
|---|--|
| Printer Compatibility:                    | HP & Troy 4200 only with two 500-sheet trays<br>HP & Troy 4250 only with two 500-sheet trays<br>HP & Troy 4350 only with two 500-sheet trays<br>Consult your Formax dealer for an updated list of additional FD 2052IL-compatible laser printers |
| Fold Types:                               | Z & V (all applications), C (bottom check position only)   |
| Speed:                                    | Printer dependent  |
| Paper Size:                               | Up to 8.5" W x 14" L   |
| Power:                                    | FD Model: 120 Volts AC, 50/60 Hz<br>FE Model: 220 Volts AC, 50/60 Hz   |
| Duty Cycle:                               | Up to 175,000 pieces per month   |
| Dimensions (closed) **:                   | 17" W x 43.5" L x 16" H  |
| Dimensions w/18" Conveyor (closed):       | 17" W x 58.5" L x 16" H  |
| Tabletop Area Required:                   | 19" W x 49" L  |
| Tabletop Area Required with 18" Conveyor: | 19" W x 64" L  |
| Dimensions with Cabinets & 18" Conveyor:  | 17" W x 69" L x 45.5" H  |

\*\* Dimensions include IL Pressure Sealer and IL Alignment Base (both included) and laser printer (not included in system)

10/2006



Enclosed paper path provides optimal document security



Standard Catch Tray